

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 1 W., W. M.

CHAINS	<p>South, on a true line bet. secs. 3 and 4.</p> <p style="text-align: right;">Va.20*E.</p>
68.50	<p>Set a basalt stone 18x8x4 ins., 12 ins. in the ground for $\frac{1}{4}$ sec. cor. mkd. $\frac{1}{4}$ on W. face, from which</p> <p style="padding-left: 40px;">A live oak, 4 ins. diam., bears N.82*E., 34 lks. dist. mkd. $\frac{1}{2}$ S B T.</p> <p style="padding-left: 40px;">A matherone, 14 ins. diam., bears N.65*W., 4 lks. dist. mkd. $\frac{1}{2}$ S B T.</p>
108.50	<p>The cor. to secs. 3, 4, 9 and 10.</p> <p>Land, high, mountainous and rolling; soil, 2nd and 3rd rate. Densely covered with forest of fir, cedar, B. oak, live oak and maple.</p> <p>Thick undergrowth of maple fir and matherone. 108.50 chs.</p> <p style="text-align: right;">December 12, 1883</p>
	<p style="text-align: right;">Va.19*45'E.</p> <p>North, bet. secs. 28 and 29.</p> <p style="text-align: center;">* * * * *</p>
80.00	<p>A point about 400 ft. above spring branch and set a basalt stone 18x10x6 ins., 12 ins. in the ground for cor. to secs. 20, 21, 28 and 29, mkd. with 2 notches on S. and 4 notches on E. edges, from which</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears N.40*E., 28 lks. dist. mkd. T 32 S R 1 W S 21 B T.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S.32*E., 53 lks. dist. mkd. T 32 S R 1 W S 28 B T.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S.78*W., 19 lks. dist. mkd. T 32 S R 1 W S 29 B T.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears E.58*W., 19 lks. dist. mkd. T 32 S R 1 W S 20 B T.</p> <p>Land, high and mountainous; soil, 2nd rate. Densely covered with forest of fir, cedar, sugar pine, and yew.</p> <p>Thick undergrowth of fir, dogwood, chinquapin, arrow-wood, and matherone. 80.00 chs.</p>