

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 32 S., R. 2 W.,  
As surveyed by Charles L. Campbell, Deputy Surveyor,  
Under contract No. 747, dated May 5, 1902.

CHAINS

- North, between secs. 31 and 36 \*\*\*\*\*
- 80.00 Set an ironstone, 24x10x4 ins., 18 ins. in ground, for cor. of secs. 25, 30, 31 and 36, marked with 5 notches on N., and 1 notch on S. edges, from which
- A hemlock, 30 ins. diam., bears N.68\*E., 60 lks. dist.  
Marked T 32 S R 2 W S 30 B T.
- A hemlock, 28 ins. diam., bears S.62\*E., 25 lks. dist.  
Marked T 32 S R 2 W S 31 B T.
- A fir, 36 ins. diam., bears S.51 $\frac{3}{4}$ \*W., 30 lks. dist.  
Marked T 32 S R 3 W S 36 B T.
- A fir, 24 ins. diam., bears N.120\*W., 63 lks. dist.  
Marked T 32 S R 3 W S 25 B T.
- Land, rolling and mountainous.  
Soil, sandy, second and third rate.  
Timber, fir, hemlock and spruce.  
Undergrowth, laurel and vine maple.  
Mountainous and heavily timbered land. 80.00 chs.
- 
- North, between secs. 25 and 30.  
Ascend gradually through to scattering timber and undergrowth.
- 9.50 Top of ascent, 150 ft. above Cow Creek. Descend over ridges and ravines on West slope of mountain.
- 22.20 Spring branch, 3 lks. wide, in ravine, 150 ft. deep, course, West.
- 37.84 Spring branch, 2 lks. wide, in ravine, 50 ft. deep, course, West.
- 40.00 Set a granite stone, 18x12x12 ins., 12 ins. in ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on the West face, from which
- A matherone, 10 ins. diam., bears N.10\*E., 45 lks.  
Marked  $\frac{1}{4}$  S 30 B T.
- A fir, 38 ins. diam., bears S.17\*W., 76 lks. dist.  
Marked  $\frac{1}{4}$  S 25 B T.
- 69.80 Spring branch, 2 lks. wide, course N.70\*W.