

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 32 S., R. 2 W.

CHAINS

80.00

Set a granite stone, 24x12x5 ins., 18 ins. in the ground, for cor. of secs. 19, 24, 25 and 30, marked, 2 notches on the S. and four notches on the N. edges, from which

A fir, 24 ins. diam., bears N.52 $\frac{1}{2}$ *E., 7 lks. dist.
Marked T 32 S R 2 W S 19 B T.

A fir, 16 ins. diam., bears S.15*E., 8 lks. dist.
Marked T 32 S R 2 W S 30 B T.

A fir, 14 ins. diam., bears S.74*W., 30 lks. dist.
Marked T 32 S R 3 W S 25 B T.

A fir, 14 ins. diam., bears N.79 $\frac{1}{2}$ *W., 45 lks. dist.
Marked T 32 S R 3 W S 24 B T.

Land, mountainous.

Soil, gravelly, third rate.

Timber, fir, pine, hemlock, matherone and cedar.

Undergrowth, laurel, huckle berry and fern.

Mountainous land, 80.00 chs.

North, between secs. 19 and 24.

Descend over ridges and ravines along W. slope of mountain, through scattering timber and dense undergrowth.

31.50 Ravine, 150 ft. deep, course N.60*W.

40.00 Set a sandstone, 15x12x10 ins., 10 ins. in ground, for $\frac{1}{2}$ sect cor., marked $\frac{1}{2}$ on W. face, from which

A fir, 10 ins. diam., bears S.21*E., 71 lks. dist.

Marked $\frac{1}{2}$ S 19 B T.A hemlock, 10 ins. diam., bears N.53 $\frac{1}{2}$ *W., 103 lks.Marked $\frac{1}{2}$ S 24 B T.

58.75 Ravine, 200 ft. deep, course West.

80.00 Set an ironstone, 24x15x8 ins., 18 ins. in ground, for cor. of secs. 13, 18, 19 and 24, marked 3 notches on North and South edges, from which

A fir, 48 ins. diam., bears S.8*E., 45 lks. dist.

Marked T 32 S R 2 W S 19 B T.