

## County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 2 W.

## CHAINS

- Summit of divide, 200 ft. above creek, bears NE. and SW.  
Descend N. slope of mountain.
- 78.25 Enter scattering timber, bears NW. and SE.
- 80.00 Set an ironstone, 24x12x8 ins., 18 ins. in ground, for  
cor. of secs. 1, 11, 2, and 12, marked with 5 notches  
on S. and 1 notch on E. edges. No trees in limits  
suitable for marking.
- Raise mound of stone, 3 ft. base, 2 ft. high, W. of cor.  
Pits impracticable.
- Land, mountainous.
- Soil, sandy and gravelly, second and third rate.
- Timber, fir, hemlock, and yellow pine.
- Undergrowth, laurel, vine maple and huckleberry.
- Mountainous and heavily timbered lands.
- 
- N.89°56'E., on random line between secs. 1 and 12.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 79.60 Intersect E. Bdy. of Tp., 14 lks. N. of the cor. of secs.  
1, 6, 7, and 12, which is a stone, 4x10x6 ins. above ground  
marked and witnessed as described by the surveyor general.  
Thence, I run N.89°58'W., on true line between secs. 1 & 12.  
Ascend E. slope, through heavy timber.
- 0.07 A brush fence, bears N. and S.
- 0.30 Log cabin bears S.50 lks. dist.
- 0.70 Log cabin bears N.75 lks. dist.
- 1.21 Brush fence, bears N.10°W., and S.10°E.
- 4.50 Abrupt ascent over large boulder.
- 6.50 Foot of perpendicular bluffs, 75 ft. high, bears N. and S.
- 6.60 Top of bluffs bears N. and S. More gradual ascent over  
rolling ground.
- 13.00 Descend gradually.
- 23;32 A spring branch, 2 lks. wide, in ravine, 50 ft. deep,  
course N.20°E., ascend over small ridges and ravines.
- 39.80 Set an ironstone, 28x12x8 ins., 21 ins. in ground, for  
 $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on the N. face, from which  
A fir, 12 ins. diam., bears S.28°E., 45 lks. dist.  
Marked  $\frac{1}{4}$  S 12 B T.