

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 2 W.

CHAINS

- 95.00 Spring branch 2 lks. wide, in ravine, 10 ft. deep, course N.70*W.
- 98.20 Intersect S. Bdy. of T. 31 S R 2 W., 140 lks. E. of the $\frac{1}{4}$ sec. cor. on the S. bdy. of sec. 36.
At point of intersection set a basalt stone, 24x15x5 ins., 18 ins. in ground, for closing cor. of secs. 1 and 2, marked CC on the S. face, with 1 groove on E. and 5 grooves on W. faces, from which
A fir, 14 ins. diam., bears S.70 $\frac{1}{2}$ *E., 40 lks. dist.
Marked T 32 S R 2 W S 1 B T.
A fir, 14 ins. diam., bears S.3*W., 28 lks. dist..
Marked T 32 S R 2 W S 12 B T.
Land, mountainous.
Soil, sandy and gravelly, second and third rate.
Timber, fir and hemlock.
Undergrowth, laurel, vine maple, blackberry and buck brush.
Mountainous land.
-
- At 8.30 A.M., l.m.t., I set off 42*45'N. on the lat. arc., 4*23'N. on the decl. arc., and determine a true meridian with the solar, at standard cors. of secs. 34 and 35 on the S. Bdy. of the Tp. which is a post, 4 ins. sq., marked and witnessed as described by the surveyor general.
Thence, I run N.0*02'W., between secs. 34 and 35.
Descend N. slope through scattering timber and dense undergrowth.
- 8.00 Spring branch, 3 lks. wide, in ravine, 50 ft. deep, course N.60*E., over small ridges and ravines.
- 38.90 Dry bed of stream, 5 lks. wide, in canyon, 150 ft. deep, course S.60*E.
- 40.00 Set an ironstone, 32x12x4 ins., 24 ins. in ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on the W. face, from which