

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 2 W.

CHAINS

- 39.95 Set an ironstone, 28x15x6 ins., 21 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on the N. face, from which
- A fir, 30 ins. diam., bears N.36 $\frac{1}{2}$ *E., 45 lks. dist.
Marked $\frac{1}{4}$ S B6 B T.
- A fir, 40 ins. diam., bears S.77 $\frac{1}{2}$ *E., 38 lks. dist.
Marked $\frac{1}{4}$ S 35 B T.
- 44.50 Leave timber, bears NW. and SE.
- 46.70 Brink of great perpendicular bluffs, 150 ft. high, bears N. and S.
- 50.00 Foot of precipitous ground, bears N. and S.
- 79.90 The cor. of secs. 26, 27, 34 and 35.
- Land, mountainous.
Soil, gravelly and stony, third and fourth rate.
Timber, fir, sugar pine and hemlock.
Undergrowth, laurel, huckleberry and small firs.
Mountainous land.
-
- N.0*02*W., between secs. 26 and 27.
Ascend SW. slope of mountain through old deadening.
- 5.00 Enter live timber, bears NW. and SE.
- 17.70 Foot of perpendicular bluffs, 50 ft. high, bears E. and W.
- 40.00 Set a basalt stone, 36x24x5 ins., 27 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on the W. face, from which
- A sugar pine, 40 ins. diam., bears N.50*E., 110 lks.
Marked $\frac{1}{4}$ S 26 B T.
- A fir, 15 ins. diam., bears N.15*W., 138 lks. dist.
Marked $\frac{1}{4}$ S 27 B T.
- 64.14 A sugar pine, 42 ins. diam., on line, I mark with 2 notches on N. and S. sides.
- 65.25 Ridge point, 500 ft. above creek, bears NW. and SE.
Descend into canyon.
- 80.00 Set a basalt stone, 36x15x12 ins., 27 ins. in ground, for cor. of secs. 22, 23 26 and 27, marked with 2 notches on S. and E. edges, from which