

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 2 W.

CHAINS

- 9.45 A fir, 30 ins. diam., on line, I mark with 2 notches on N. and S. sides.
- 40.00 Set an ironstone, 18x10x5 ins., 12 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on the W. face, from which
 A fir, 24 ins. diam., bears S.88*E., 27 lks. dist.
 Marked $\frac{1}{4}$ S 10 B T.
 A fir, 30 ins. diam., bears S.43*W., 44 lks. dist.
 Marked $\frac{1}{4}$ S 9 B T.
- 40.45 Spring branch, 3 lks. wide, in ravine, 100 ft. deep, course S. 80*W.
- 43.50 Enter scattering timber and dense laurel thickets, bears E. and W.
- 80.00 Set a basalt stone, 24x10x10 ins., 18 ins. in ground, for cor. of secs. 3, 4, 9 and 10, marked with 5 notches on S. and 3 notches on E. edges, from which
 A fir, 14 ins. diam., bears S.77*E., 60 lks. dist.
 Marked T 32 S R 2 W S 10 B T.
 A fir, 8 ins. diam., bears S.21*W., 23 lks. dist.
 Marked T 32 S R 2 W S 9 B T.
 A fir, 40 ins. diam., bears N.48*W., 78 lks. dist.
 Marked T 32 S R 2 W S 4 B T.
- Land, mountainous.
 Soil, sandy, third rate.
 Timber, fir, yellow pine, sugar pine and tamarack.
 Undergrowth, laurel.
 Mountainous and heavily timbered lands.
-
- S.89*57'E. on a random line between secs. 3 and 10.
- 40.00 Set temp $\frac{1}{4}$ sec. cor.
- 79.64 Intersect N. and S. line, 14 lks. N. of the cor. of secs. 2, 3, 10 and 11.
 Thence, I run N.89*51'W. on a true line between secs. 3 and 10.