

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 2 W.

CHAINS	
	<p>No trees in limits. Raise mound of stone, 3 ft. base, 2 ft. high, W. of cor. Pits impracticable.</p>
47.15	Trail to Rawley's Copper Mine, bears NE. SW.
53.50	Leave old burn and enter heavy timber, bears E. and W.
98.24	Intersect S. Bdy. of T 31 S R 2 W, 160 lks. E. of the $\frac{1}{4}$ sec. cor. on the S. bdy. of sec. 34.
	<p>At point of intersection, set an ironstone, 18x12x12 ins., 12 ins. in ground, for closing cor. of sec. 3 and 4, marked C. C. on the S. face, with 3 grooves on the E. and W. faces, from which</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S.66*E., 38 lks. dist. Marked T 32 S R 2 W S 3 B T.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S.36*W., 29 lks. dist. Marked T 32 S R 2 W S 4 B T.</p>
	<p>Land, mountainous. Soil, gravelly, third rate. Timber, fir, hemlock, pine and maple. Undergrowth, laurel, huckle berry and vine maple. Mountainous land.</p>
	<p>Thence, I run N.0*04'W. between secs. 32 and 33. Ascend S. slope, through scattering timber and dense undergrowth.</p>
37.00	Ridge point, 300 ft. above sec. cor., descends toward the SE.
40.00	<p>Set an ironstone, 24x10x10 ins., 18 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on the W. face, from which</p> <p style="padding-left: 40px;">A hemlock, 20 ins. diam., bears N.15*E., 61 lks. Marked $\frac{1}{4}$ S 33 B T.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N.75*W., 51 lks. dist. Marked $\frac{1}{4}$ S 32 B T.</p>
50.37	A fir, 38 ins. diam., on line, I mark with 2 notches on N. and S. sides.