

County Surveyor's Record, Douglas County, Oregon

Subdivisions T. 32 S., R. 2 W.

CHAINS

- 67.13 A fir, 48 ins. diam., on line, I mark with 2 notches on N. and S. sides.
- 80.00 Set an ironstone, 28x12x12 ins., 21 ins. in ground, for cor. of secs. 20, 21, 28, and 29, marked with 2 notches on S. and 4 notches on E. edges, from which
- A fir, 20 ins. diam., bears N.10 $\frac{1}{2}$ *E., 41 lks. dist.
Marked T 32 S R 2 W S 21 B T.
- A fir, 36 ins. diam., bears S.77 $\frac{1}{2}$ *E., 34 lks. dist.
Marked T 32 S R 2 W S 28 B T.
- A fir, 48 ins. diam., bears S.73*W., 38 lks. dist.
Marked T 32 S R 2 W S ²29 B T.
- A fir, 28 ins. diam., bears N.19 $\frac{3}{4}$ *W., 35 lks. dist.
Marked T 32 S R 2 W S 20 B T.
- Land, mountainous.
- Soil, gravelly, third rate.
- Timber, fir, hemlock and yellow pine.
- Undergrowth, laurel.
- Mountainous and heavily timbered lands.
-
- 40.00 N.89*51'E., on a random line between secs. 21 and 28
Set temp. $\frac{1}{4}$ sec. cor.
- 80.20 Intersect N. and S. line, 35 lks. N. of the cor. of secs. 21, 22, 27 and 28.
Thence, I run N.89*54'W., on a true line between secs. 21 and 28.
Descend along N. slope of mountain, through heavy timber.
- 6.87 Peavine Creek, 3 lks. wide, in ravine, 50 ft. deep,
course N.60*W.
- 13.90 Spring branch, 2 lks. wide, in ravine, 10 ft. deep, course North. Ascend gradually over small ridges and ravines.
- 22.20 A fir, 30 ins. diam., on line, I mark with 2 notches on N. and S. sides.
- 40310 Set an ironstone, 30x12x8 ins., 23 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on the N. face, from which