

Subdivisions-T. 32 S., R. 2.W.

CHAINS	
79.00	Steep descent of N. slope into Drews Creek, Canyon
80.00	<p>Set an ironstone, 24x10x10 ins., 18 ins. in ground, for cor. of secs. 4, 5, 8 and 9, marked with 5 notches on S. and 4 notches on E. edges, from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N.61°E., 45 lks. dist. Marked T 32 S R 2 W S 4 B T.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N.46½°W., 15 lks. dist. Marked T 32 S R 2 W S 5 B T.</p>
	<p>No other trees in limits. Raise mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Pits impracticable.</p> <p>Land, mountainous.</p> <p>Soil, gravelly third rate.</p> <p>Timber, fir and hemlock.</p> <p>Undergrowth, laurel and small firs.</p> <p>Mountainous and densely overgrown lands.</p>
	<p>N.89°51'E. on a random line between secs. 4 and 9.</p>
40.00	Set temp. ¼ sec. cor.
80.10	<p>Intersect N. and S. line, 5 lks. S. of the cor. of secs. 3, 4, 9 and 10.</p>
	<p>Thence, I run S.89°49'W. on a true line between secs. 4 and 9. Ascend gradually along N. slope, through scattering timber and undergrowth.</p>
2.50	<p>Ridge point, 10 ft. above sec. cor., bears NW. and SE. Descend along SW. slope into Drews Creek.</p>
40.05	<p>Set an ironstone, 24x10x8 ins., 18 ins. in ground, for ¼ sec. cor., marked ¼ on the N. face, from which</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears N.31½°E., 25 lks. dist. Marked ¼ S 4 B T.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S.89°W., 45 lks. dist. Marked ¼ S 9 B T.</p>
55.00	Precipitous descent into Drews Creek.
62.50	<p>Foot of mountain, 300 ft. below top of ridge, bears N.60°W. and S.60°E.</p>