

Subdivisions T. 32 S., R. 2 W.

CHAINS

- 98.36 Intersect S. Bdy. of T. 32 S. R. 2 W, 145 lks., E. of the  $\frac{1}{4}$  sec. cor. on the S. Bdy. of Sec. 33. At point of intersection, set a basalt stone, 18x8x5 ins., 12 ins. in ground, for closing corner of secs. 4 and 5, marked C. C. on the S. face, with 4 grooves on the E. and 2 grooves on the W. faces, from which
- A fir, 30 ins. diam., bears S.53\*E., 18 lks. dist.  
Marked T 32 S R 2 W S 4 B T.
- A fir, 30 ins. diam., bears S.77\*W., 37 lks. dist.  
Marked T 32 S R 2 W S 5 B T.
- Land, mountainous.
- Soil, gravelly and stony, third and fourth rate.
- Timber, fir, hemlock, yellow pine, alder, maple and matherone.
- Undergrowth, laurel, vine maple and huckle berry.
- Mountainous land.
- 
- Thence, I run N.0\*05'W., between secs. 31 and 32.
- Ascend S. slope of mountain, through heavy timber and dense undergrowth.
- 11.75 Divide between Rogue and Umpqua Rivers, 250 ft. above sec. cor., bears N.60\*E. and S.60\*W. Descend N. slope of mountain.
- 13.00 Enter scattering timber, bears E. and W.
- 40.00 Set an ironstone, 24x10x4 ins., 18 ins. in ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on the W. face, from which
- A fir, 24 ins. diam., bears N.85\*E., 17 lks. dist.  
Marked  $\frac{1}{4}$  S 32 B T.
- A fir, 28 ins. diam., bears S.80\*W., 105 lks. dist.  
Marked  $\frac{1}{4}$  S 31 B T.
- 53.00 Enter heavy timber, bears E. and W.
- 56.25 Spring branch, 3 lks. wide, in ravine, 50 ft. deep, course NW. More gradual descent.