

## County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 2 W.

## CHAINS

- 80.10 The cor. of secs. 7, 8, 17 and 18.  
Land, mountainous.  
Soil, gravelly, third rate.  
Timber, scattering, black pine and firs.  
Undergrowth, dense laurel, chinquapin and matherone.  
Mountainous land. 80.10 chs.
- 
- N.0\*05\*W., between secs. 7 and 8.  
Descend N. slope of mountain through scattering timber  
and dense undergrowth.
- 13.00 Foot of mountain, 400 ft. below summit of divide, bears  
S.80\*W. and N.80\*E., Cow Creek, 25 lks. wide, 1 ft.  
deep, swift current, sandy bottom, course S.80\*W.  
Ascend steep S. slope of mountain.
- 40.00 Set a maple post, 6 ins. sq., 3 ft. long, 24 ins. in  
ground, for  $\frac{1}{2}$  sec. cor., marked  $\frac{1}{2}$  S 7 on W. and S 8 on  
the E., faces, from which  
An alder, 8 ins. diam., bears N.30\*E., 30 lks.  
Marked  $\frac{1}{2}$  S B T.  
A hemlock, 10 ins. diam., bears N.40\*W., 38 lks.  
Marked  $\frac{1}{2}$  S B T.
- 70.50 Enter heavy timber, bears E. and W.
- 77.00 Ravine, 75 ft. deep, course S.60\*E.
- 79.50 Enter scattering timber, bears E. and W.
- 80.00 Set an ironstone, 15x12x8 ins., 12 ins. in ground, for  
cor. of secs. 5, 6, 7, and 8, marked with 5 notches  
on S. and E. edges, from which  
A fir, 30 ins. diam., bears S.8\*E., 71 lks. dist.  
Marked T 32 S R 2 W S 8 B T.  
A fir, 12 ins. diam., bears S.24 $\frac{1}{2}$ \*W., 45 lks. dist.  
Marked T 32 S R 2 W S 7 B T.
- No other trees in limits. Raise mound of stone, 2 ft.  
base, 1 $\frac{1}{2}$  ft. high, W. of cor. Pits impracticable.