

County Surveyor's Record, Douglas County, Oregon

8355

Dependent resurvey of East Bdy. T. 32 S., R. 3 W.
As surveyed by Fred Mensch, U. S. Surveyor,
Under special instructions, dated August 20, 1912..

CHAINS	
80.00	<p>At the standard cor. of Tps. 32 S., Rs. 2 and 3 W., Thence I run North, on true line along the E. bdy. of sec. 36 ***** Set a basalt stone, 15x12x8 ins., 10 ins. in ground, for cor. of secs. 25 and 36 only, marked with 1 notch on S. and 5 notches on N. edge, from which An alder, 20 ins. diam., bears S.17*W., 143 lks. Marked T 32 S R 3 W S 36 B T. A yew, 9 ins. diam., bears N.70*W., 23 lks. dist. Marked T 32 S R 3 W S 25 B T.</p> <p>Land, mountainous. Soil, decomposed granite, third rate. Timber, fir, hemlock, chinquapin and yew. Undergrowth, fir, hemlock and rhododendron.</p>
7.98	<p>At the cor. of secs. 25 and 36. Thence I run N.0*45'S. on the true line along the E. bdy. of sec. 25. Ascend S. slope through dead timber and undergrowth. Intersect the old cor. of secs. 25, 30, 31 and 36 which is a stone, firmly set in the ground, marked and witnessed as described by the Surveyor General. I now change this cor. to refer to secs. 30 and 31, T. 32 S., R. 2 W., only by obliterating marks on bearing trees referring to T. 32 S., R. 3 W.</p> <p>I continue my measurements N.0*30'E., on a true line along the E. bdy. of sec. 25. Ascend SW. slope.</p>
15.00	Ridge, bears NE. and SW. Descend NW. slope.
29.90	Creek, 2 lks. wide, course NW. Ascend SW. slope.
35.00	Spur, slopes W. Descend NW. slope.
36.50	Ravine, course W. Ascend SW. slope.