

Depend. Resurvey of E. bdy. of T. 32 S., R. 3 W.

CHAINS

- 40.00 Set a granite stone, 16x8x6 ins., 11 ins. in ground, for $\frac{1}{4}$ sec. cor. for sec. 25 only, marked $\frac{1}{4}$ on W. face, from which
- A fir, 50 ins. diam., bears S.77*W., 52 lks. dist.
Marked $\frac{1}{4}$ S 25 B T.
- A fir, 36 ins. diam., bears N.21*W., 84 lks. dist.
Marked $\frac{1}{4}$ S 25 B T.
- 41.00 Spur, slopes W., enter green timber, bears E. and W. Descend NW. slope.
- 45.55 Creek, 2 lks. wide, course W., ascend SW. slope.
- 47.77 Intersect the old $\frac{1}{4}$ cor. of secs. 25 and 30, which is a stone, firmly set, marked and witnessed as described by the Surveyor General. I now change this cor. to refer to sec. 30 only, as follows:
- I destroy the marks on W. and mark $\frac{1}{4}$ on E. face of stone, for $\frac{1}{4}$ cor. of sec. 30, T. 32 S., R. 2 W., only, from which
- A madrona, 10 ins. diam., bears N.1*30'E., 45 lks.
Marked $\frac{1}{4}$ S 30 B T.
- A yew, 12 ins. diam., bears S.5*30'E., 107 lks. dist.
Marked $\frac{1}{4}$ S 30 B T.
- I destroy the marks on former bearing tree in sec. 25. I continue my measurements, N.0*26'E., on a true line along the E. bdy. of sec. 25.
- 57.20 Spur, slopes SW. descend NW. slope.
- 59.10 Ravine, course SW., ascend SW. slope.
- 71.50 Spur, slopes W., descend NW. slope.
- 76.60 Creek, 2 lks. wide, course NW., ascend SW. slope.
- 80.00 Set a granite stone, 15x12x6 ins., 10 ins. in ground, for cor. of secs. 24 and 25 only, marked with 2 notches on S. and 4 notches on N. edge, from which
- A sugar pine, 12 ins. diam., bears S.82*W., 25 lks.
Marked T 32 S R 3 W S 25 B T.
- A fir, 12 ins. diam., bears N.60*W., 45 lks. dist.
Marked T 32 S R 3 W S 24 B T.