

County Surveyor's Record, Douglas County, Oregon

8359

Portion of West Boundary of T. 32 S., R. 3 W.,
as surveyed by W. H. Byars, Deputy Surveyor
under Contract No. 152, dated June 3, 1871.

CHAINS		
	From the corner to Tps. 31 and 32 S., Rgs. 3 and 4 W., I run South on the West Bdy. of Tp. 32 S., R. 3 W. South, on a true line, bet. Secs. 1 and 6. Va. 20° E.	
5.00	To foot of steep mountain.	
22.50	Top of spur, course NE. along East slope.	+1000
35.00	A spring, course East.	+ 950
40.00	Set $\frac{1}{4}$ Sec. post, from which A Fir, 10 ins. diam., bears N. 68° E., 8 lks. dist. A Chinquapin, 8 ins. diam., bears S. 65° W., 4 lks. dist.	+1000
58.00	A Stream, 2 lks. wide, course SE.	+ 100
64.72	A stream, 2 lks. wide, course SE.	+ 100
68.25	A stream, 3 lks. wide, course East.	+ 100
80.00	Set post, cor. to Secs. 1, 6, 7 and 12, from which A Fir, 30 ins. diam., bears N. 22° E., 20 lks. dist. A Chinquapin, 6 ins. diam., bears S. 10° E., 37 lks. dist. A Fir, 8 ins. diam., bears S. 50° W., 35 lks. dist. A Chinquapin, 5 ins. diam., bears N. 65° W., 41 lks. dist. Land, rough and mountainous; 3rd rate. Timber, 2nd rate. Fir, Chinquapin, Laurel, Cedar, Yew and a few Oaks and Pines.	+1200
	South, on a true line bet. Secs. 7 and 12. Va. 20° E.	
8.00	Top of spur, course NE. along East slope of mountain.	500
27.50	A Creek, 3 lks. wide, course East.	-700
40.00	Set $\frac{1}{4}$ Sec. post, from which A Fir, 30 ins. diam., bears N. 60° E., 31 lks. dist. A Fir, 24 ins. diam., bears S. 85° W., 31 lks. dist.	
52.00	Top of spur, course East.	+500