

County Surveyor's Record, Douglas County, Oregon

East Bdy. of Tp. 32 S., R. 4 W.

CHAINS

ground for cor. of Secs. 7, 12, 13 and 18, marked T 32 S S 7 on NE, R 3 W S 18 on SE, S 13 on S W and R 4 W, S 12 on NW faces, with 2 notches on N and 4 notches on S edges, from which

A Fir, 12 ins. diam. bears N.32*E., 76 lks. dist., marked T 32 S, R 3 W, S 7 B T.

A Fir, 24 ins. diam., bears S.72*E., 56 lks. dist., marked T 32 S R 3 W S 18 B T.

A Laurel, 20 ins. diam., bears S.50*W., 20 lks. dist., marked T 32 S R 4 W S 13 B T.

A Fir, 36 ins. diam., bears N.28*W., 31 lks. dist., marked T 32 S R 4 W S 12 B T.

Thence, I run South, on a true line between Secs. 13 and 18.

Ascend.

3.00 Spur, sloping NE. about 50 ft. above cor. Ascend along hillside, sloping SE.

14.00 Spur, sloping SE. about 75 ft. above spur last noted. Descend.

25.25 Creek, 1 lk. wide, course East about 50 ft. below last spur.

Ascend.

26.33 A Fir tree, on line, 30 ins. in diam. I mark with two n notches on North and South faces.

29.50 Top of spur, sloping SE. 25 ft. above creek; continue ascent.

36.50 Top of spur, sloping East, 25 ft. above last spur. Descend.

40.00 Set a Chinquapin post, 3½ ft. long, 4 ins. sq., 24 ins. in the ground for ¼ cor., marked ¼ South on West face, from which

A Chinquapin, 6 ins. diam., bears N.60*E., 13 lks. dist., marked ¼ S B T.