

East Bdy. of T. 32 S., R. 4 W.

CHAINS
40.00

Set a basalt stone 14 x 8 x 8 ins., 9 ins. in the ground, for $\frac{1}{4}$ Sec. cor., marked $\frac{1}{4}$ South on West face, from which

A Cedar, 20 ins. diam., bears N.68*E., 8 lks. dist., marked $\frac{1}{4}$ S B T.

A Fir, 18 ins. diam., bears S.82*W., 7 lks. dist., marked $\frac{1}{4}$ S B T.

This cor. is on a hillside, sloping NW. about 300 ft. above creek.

43.50 Top of spur, sloping East 20 ft. above $\frac{1}{4}$ Sec. cor.; ascend along hillside, sloping East.

46.50 Cove, sloping East.

53.00 Top of ridge, bears NE. and SW. This is the divide between the head waters of the Umpqua and Rogue rivers; about 500 ft. above $\frac{1}{4}$ Sec. cor.

Leave green timber, bearing NE. and SW., and descend over rocky mountain side.

79.00 Enter green timber, bears East and West.

80.00 Set a basalt stone, 16 x 12 x 10 ins., 10 ins. in the ground, for cor. of Secs. 30, 31, 36 and 25, marked with 5 notches on North and 1 notch on South edges, from which

A Fir, 24 ins. diam., bears N.40*E., 79 lks. dist., marked T 32 S R 3 W S 30 B T.

A Fir, 24 ins. diam., bears S.60*E., 22 lks. dist., marked T 32 S R 3 W S 31 B T.

A Fir, 24 ins. diam., bears S.75*W., 33 lks. dist., marked T 32 S R 4 W S 36 B T.

A Pine, 12 ins. diam., bears N.1*W., 104 lks. dist., marked T 32 S R 4 W S 25 B T.

This cor. is on a hillside, sloping South about 500 ft. below top of ridge.

Land, mountainous.