

## County Surveyor's Record, Douglas County, Oregon

25

## East Boundary of T. 32 S., R. 4 W.

CHAINS

The mines are placer and are interspersed throughout the vicinity.

Carl S. Nicklin,

U.S. Deputy Surveyor.

August 17, 1897.

---

Subdivisions of T. 32 S., R. 3 W.  
as surveyed by Fred Mensch, Deputy Surveyor,  
under Contract No. 757, dated Sept. 14, 1904.

---

I commence at the corner of Secs. 1, 2, 11 and 12.

Thence I run

East, between Secs. 1 and 12.

Over mountainous land, heavily timbered and covered with dense undergrowth.

11.00 Cow Creek, 30 lks. wide, course S.80\*W.

19.00 Ascend steep NW. slope.

22.00 Ridge point, descending North.

Descend NE. slope.

25.75 Cow Creek, 40 lks. wide, course N.65\*W.

33.50 Trail, bears NW. and SE.

39.80 The corner which I established in my original survey under Contract No. 757 as the  $\frac{1}{4}$  Sec. corner between Secs. 1 and 12, bears South 20 lks. dist. I destroy marks on corner and bearing trees.

40.00 Set a Basalt stone, 14x10x8 ins., 10 ins. in the ground for  $\frac{1}{4}$  Sec. cor., marked  $\frac{1}{4}$  on North face, from which

A Pine, 10 ins. diam., bears N.3\*E., 29 lks. dist., marked  $\frac{1}{4}$  S 1 B T.

A Fir, 7 ins. diam., bears S.36\*W., 10 lks. dist., marked  $\frac{1}{4}$  S 12 B T.

54.00 Ravine, course South.

60.50 Summit of ridge, bears North and South.

63.00 Ravine, course South.