

Subdivisions of T. 32 S. R. 3 W.

| CHAINS | |
|--------|---|
| | Over mountainous land through dense undergrowth. |
| 1.00 | Summit of divide, between Applegate and Cow creeks, bears NW. and SE. Descend SW. slope. |
| 16.50 | Gulch, course West. Enter heavy timber, bears East and West. Ascend NW. slope. |
| 24.50 | Summit of ridge bears NE. and SW. Descend South slope. |
| 32.50 | Gulch, course SW. |
| 39.00 | Creek, 5 lks. wide, course West. |
| 40.00 | Set an ironstone 12x8x6 ins., 8 ins. in the ground for $\frac{1}{4}$ on West face, from which A Red Fir, 16 ins. diam., bears N.64*E., 32 lks. dist., marked $\frac{1}{4}$ S 13 B T. A Maple, 8 ins. diam., bears N.26*W., 13 lks. dist., marked $\frac{1}{4}$ S 14 B T. Ascend North slope. |
| 56.00 | Summit of ridge, bears East and West. Descend SW. slope. |
| 74.50 | Gulch, course West. |
| 77.50 | Gulch, course West. |
| 80.00 | Set a slate stone 15x12x8 ins., 10 ins. in the ground for cor. of Secs. 13, 14, 23 and 24, marked with 3 notches on South and 1 notch on East edge, from which A Hemlock, 8 ins. diam., bears N.68*E., 37 lks. dist., marked T 32 S R 3 W S 13 B T. A White Fir, 12 ins. diam., bears S.10*E., 26 lks. dist., marked T 32 S R 3 W S 24 B T. A Hemlock, 10 ins. diam., bears S.82*W., 48 lks. dist., marked T 32 S R 3 W S 23 B T. A Red Fir, 18 ins. diam., bears N.18*W., 30 lks. dist., marked T 32 S R 3 W S 14 B T. |