

34
County Surveyor's Record, Douglas County, Oregon

Resurvey of Subdivisions of T. 32 S., R. 3 W.

CHAINS

A Red Fir, 30 ins. diam., bears S.27*W., 23 lks. dist., marked $\frac{1}{4}$ S 11 B T.

50.48 Creek, 2 lks. wide, C. NW.
Ascend gradually along W. slope.

61.00 Gulch, C. W.

68.75 Ridge point.
Descend N. slope.

75.50 Cow Creek, 50 lks. wide, C. NW.

80.48 The cor. of Secs. 1, 2, 11 and 12.
Land, mountainous.
Soil, loam and stony; 2nd and 3rd rate.
Timber, Red Fir, Sugar and Yellow Pine, Cedar, Laurel.
Undergrowth, arrowwood, hazel, chinquapin, vinemaple.
Mountainous or heavily timbered land, or land covered with dense undergrowth, 80.48 chs.

September 2, 1905

Retracement-Re-establishment of E. Bdy.
of Tp. 32 S., R. 4 W., as surveyed by Fred Mensch,
under Special Instructions, dated August 20, 1912.

At the closing cor. of Tps. 32 S., Rgs. 3 and 4 W.
Thence I run
North, retracing the E. bdy. of Sec. 36.
Ascend SE. slope, through dense timber and undergrowth.
26.00 Ridge, bears NE. and SW.; descend NW. slope.

42.00 Leave heavy timber, bears NE. and SW.; ascend through
low Buck Horn, Manzanita and live Oak.

50.90 Spur, slopes SE.; descend NE. slope.

59.81 Fall 33 lks. E. of the $\frac{1}{4}$ cor. of Secs. 31 and 36, which
is a stone, firmly set, marked and witnessed as de-
scribed by the Surveyor General. I now change this
cor. to refer to Sec. 36 only, and re-witness as
follows:

A Madrona, 6 ins. diam., bears S.57*W., 200 lks.
dist., marked $\frac{1}{4}$ S 36 B T.