

## Retracement-Reestablishment of East Bdy. of T. 32 S. R. 4 W.

CHAINS

At the cor. of Secs. 19, 24, 25 and 30, I set off

10\*40'30"S. \*\*\*\*\*

Thence, I retrace South along the East Bdy. of Sec. 25 and at 39.68 chs., fall 73 lks. East of the  $\frac{1}{4}$  Sec. cor. Commencing again at the  $\frac{1}{4}$  Sec. cor. I continue the re-tracement South and at 40.05 chs. fall 205 lks. East of the cor. of Secs. 25 and 36.

Thence, I run

N.2\*56'E. on a true line along the East Bdy. of Sec. 25.

Ascend South slope through scattering timber and dense undergrowth.

- 5.00 Leave scattering timber, bears East and West; ascend through low Buck Horn, Manzanita and live Oak.
- 27.00 Summit of Umpqua Divide, bears East and West.  
Enter heavy timber, bears East and West; ascend NE. slope.
- 28.60 Trail, bears East and West.
- 37.25 Rocky spur, slopes NE.; descend steep, rocky NW. slope.
- 40.10 Intersect the  $\frac{1}{4}$  cor. of Secs. 25 and 30, which is a stone, firmly set, marked and witnessed as described by the Surveyor General. I now change this cor. to refer to Sec. 25 only, and rewitness as follows: From the cor.
- A Fir, 18 ins, diam., bears S.82\*W., 7 lks. dist., marked  $\frac{1}{4}$  S 25 B T.
- A Fir, 30 ins. diam., bears N.21\*W., 41 lks. dist., marked  $\frac{1}{4}$  S 25 B T.
- I destroy the marks on former bearing tree referring to Sec. 30.
- I continue my measurements.
- N.1\*03'E. on a true line along the East Bdy. of Sec. 25.
- 54.00 Snow Creek, 5 lks. wide, course SE.; along East slope.
- 60.00 Ascend SE. slope.