

Retracement-Reestablishment of East Bdy. of T. 32 S. R. 4 W.

CHAINS

7.00 Spur, slopes N.75*E.

9.20 Ravine, course NE.
Leave heavy timber, bears East and West; ascend SE. slope through old burn.

19.20 Spur. slopes East; descend East slope.

25.00 Enter heavy timber, bears East and West.

32.25 Creek, 3 lks. wide, course NE.; ascend SE. slope.

37.40 Creek, 2 lks. wide, course N.60*E.

38.87 Intersect the cor. of Secs. 13, 18, 19 and 24, which is a stone, firmly set, marked and witnessed as described by the Surveyor General, except that the old bearing trees in Secs. 18 and 19 have been destroyed by fire. I now change this cor. to refer to Secs. 13 and 24 only.

Land, mountainous.

Soil, stony clay loam; third rate.

Timber, Fir, Madrona and Chinquapin.

Undergrowth, Snow brush, Rhododendron, Chinquapin and Fir.

October 24, 1913.

At the cor. of Secs. 7, 12, 13 and 18, I set off 12*46'S.***
Thence, I retrace South between Secs. 13 and 18, and at 40.25 chs. fall 18 lks. East of the $\frac{1}{2}$ Sec. cor. I commence again at the $\frac{1}{2}$ Sec. cor. and continue the retracement South; at 39.74 chs. I fall 80 lks. East of the cor. of Secs. 13 and 24.

Thence, I run

N.1*09'E., on a true line, between Secs. 13 and 18.

Ascend SE. slope through dense timber and undergrowth.

1.70 Spur, slopes SE.; along East slope.

5.80 Spring, course SE.

13.00 Spur, slopes East. descend NE. slope.

22.00 Creek, 2 lks. wide, course NE.; ascend SE. slope.

34.30 Spur, slopes East.; descend NE. slope.