

Retracement-Reestablishment of Subdivision Lines of T. 32 S., R. 3 W.

CHAINS

and witness as follows:

From corner already set,

A Pinion, 5 ins. diam., bears N.79*E., 37 lks. dist., marked $\frac{1}{4}$ S 13 B T.

A Fir, 12 ins. diam., bears N.7*W., 48 lks. dist., marked $\frac{1}{4}$ S 13 B T.

I destroy the marks on former bearing tree, referring to Sec. 24.

63.60 Sloping rock, 25 ft. high.

76.00 Ridge, divide between Cow and Applegate creeks, bears NE. and SW; descend along North slope.

97.13 Intersect cor. of Secs. 13, 14, 23 and 24, which is a stone, firmly set in the ground, marked and witnessed as described by the Surveyor General, and which I now change to refer to Secs. 13 and 14 only, and destroy the marks on the former bearing trees in Secs. 23 and 24.

Land, mountainous.

Soil, to 23 chs. decomposed granite; 3rd rate. To 97.13 chs. stony clay loam, 3rd rate.

Timber, Fir, Hemlock and Cedar.

Undergrowth, Lilac, Rhododendron, Fir and Hemlock.

October 6, 1913.

At the cor. of Secs. 11, 12, 13 and 14.

Thence, I retrace

South, bet. Secs. 13 and 14, and at 39.99 chs. intersect the $\frac{1}{4}$ Sec. corner.

Commencing again at the $\frac{1}{4}$ Sec. corner I continue the retracement South, and at 38.92 chs. intersect the corner of Secs. 13 and 14.

Thence I run

North, on a true line, bet. Secs. 13 and 14.

Descend North slope, through dense timber and undergrowth.