

Retracement and Reestablishment of  
Subdivision Lines of T. 32 S., R. 3 W.

## CHAINS

1.80 Creek, 2 lks. wide, course NW. Ascend SW. slope.  
26.00 Ridge, bears East and West. Descend NW slope.  
29.00 Spur, slopes NW. Descend steep North slope.  
38.92 Intersect the  $\frac{1}{4}$  Sec. corner which is a stone, firmly  
set, marked and witnessed as described by the Surveyor  
General.  
40.00 Creek, 2 lks. wide, course NW. Ascend South slope.  
56.00 Ridge, bears NE and SW. Descend North slope.  
62.40 Creek, 1 lk. wide, course West. Ascend SW. slope,  
through dense thicket of young Pinon.  
78.00 Ridge, divide between Applegate and Cow Creeks, bears  
NW and SE.  
Enter heavy timber, bears NW. and SE.  
78.91 Intersect the cor. of Secs. 11, 12, 13 and 14, which  
is a stone, firmly set in the ground, marked and  
witnessed as described by the Surveyor General.  
Land, mountainous.  
Soil, decomposed granite; 3rd rate.  
Timber, Fir, Hemlock, Cedar and Madrona.  
Undergrowth, Pinon, Snow Brush and Rhododendron.  
September 17, 1913.

---

At the cor. of Secs. 14, 15, 22 and 23.

Thence I retrace

North, bet. Secs. 14 and 15, and at 39.02 chs. I fall  
124 lks. East of the  $\frac{1}{4}$  Sec. corner.

Commencing again at the  $\frac{1}{4}$  Sec. cor., I continue the  
retracement North, and at 39.28 chs. fall 41 lks.  
West of the cor. of Secs. 10, 11, 14 and 15.

The corner of Secs. 10, 11, 14 and 15 is a badly decayed  
post, marked and witnessed as described by the Survey-  
or General. I now destroy this cor. and reestablish