

## Retracement and Reestablishment of Subdivisions Lines of T.32 S., R 3 W

CHAINS	
7.35	Spur, slopes S., along S slope.
13.25	Spur, slopes S. Descend SW. slope.
31.00	Creek, 5 lks. wide, course N.25*W. Ascend NE slope.
38.15	Spur, slopes NW. Descend SW. slope.
39.74	Intersect the point for $\frac{1}{4}$ cor. of secs. 15 and 22, located by reference to the bearing trees. All other traces of cor. have disappeared. I reestablish this cor. in its original position for sec. 15 only as follows: Set a basalt stone, 15x10x6 ins., 10 ins. in the ground, for $\frac{1}{4}$ sec. cor., for sec. 15 only, marked $\frac{1}{4}$ on N. face; from which A Fir, 24 ins. diam., bears N.37*E., 25 lks. dist., marked $\frac{1}{4}$ S 15 B T. A Fir, 20 ins. diam., bears N. 30* W., 37 lks. dist., marked $\frac{1}{4}$ S 15 B T. I destroy the marks on the bearing tree S. of line. The true course and distance of this line is West, 39.74 chs.
47.35	Wagon road bears N. and S.
52.64	Applegate creek, 20 lks. wide, course N.; ascend along N. slope.
67.34	Ravine, course NE.
78.54	Spur, slopes S. Descend SW. slope.
79.06	Fall 14 lks. N. of the cor. of secs. 15, 16, 21 and 22, which is a decayed post, marked and witnessed as described by the Surveyor General, except that the SE. bearing tree is missing. I destroy this cor. and reestablish it in the same place, for the cor. of secs. 15 and 16 only, as follows: Set a granite stone, 18 x 12 x 5 ins., 12 ins. in the ground, for cor. of secs. 15 and 16, only, marked with 3 notches on E. edge from which