

Retracement-Reestablishment of Subdivision Lines of T. 32 S., R. 3 W.

CHAINS

A Fir, 18 ins. diam., bears S.34*W., 42 lks. dist.,
marked T 32 S R 3 W S 16 B T.

A Fir, 18 ins. diam., bears N.43*W., 59 lks. dist.,
marked T 32 S R 3 W S 9 B T.

Thence I run

S.0*52'E., on a true line, between Secs. 15 and 16.

Along East slope, through dense timber and undergrowth.

0.50 Spur, slopes SE. Descend SE. slope.

13.30 Dismal creek, 10 lks. wide, course NE. Ascend along
creek.

14.40 Dismal creek, 10 lks. wide, course NW.

17.50 Dismal creek, 10 lks. wide, course NE.

22.15 Dismal creek, 10 lks. wide, course NW.

23.95 Settlers trail, bears NE. and SW.

26.80 Dismal creek, 10 lks. wide, course NE. Ascend NW. slope.

36.00 Ravine, course NW. Ascend North slope.

37.29 Intersect the $\frac{1}{4}$ Sec. cor., which is a badly decayed post,
marked as described by the Surveyor General. The
East bearing tree is uprooted. No trace of the West
bearing tree can be found. I destroy this cor. and
reestablish it in the same place as follows:

Set a granite stone, 20 x 15 x 12 ins., 15 ins. in the
ground, for $\frac{1}{4}$ Sec. cor., marked $\frac{1}{4}$ on West face. from
which

A Fir, 40 ins. diam., bears N.25*E., 67 lks. dist.,
marked $\frac{1}{4}$ S 15 B T.

A Fir, 48 ins. diam., bears N.30*W., 13 lks. dist.,
marked $\frac{1}{4}$ S 16 B T.

I continue my measurements

S.0*28*W., on true line between Secs. 15 and 16.

39.50 Spur, slopes SW. Ascend NW. slope.

43.20 Ravine, course NW.

48.50 Spur, slopes NW.