

Retracement-Reestablishment of Subdivision Lines of T. 32 S., R. 3 W.

CHAINS	
	S.0*56'E., on true line, between Secs. 16 and 17.
	Descend SW. slope, through dense timber and undergrowth.
5.25	Ravine, course West; ascend NW. slope.
10.00	Ridge, divide between Snow and Dismal creeks, bears NE. and SW.
	Descend SE. slope.
13.25	Spur, slopes SE.
15.00	Ravine, course SE.
21.50	Spur, slopes SE.
25.30	Ravine, course SE. Ascend NE. slope.
33.65	Ridge, bears NW. and SE. Descend SW. slope.
40.72	Apportioned distance.
	Set a granite stone, 15x14x6 ins., 10 ins. in the ground, for $\frac{1}{4}$ Sec. cor., marked $\frac{1}{4}$ on West face, from which
	A Fir, 14 ins. diam., bears N.52'E., 36 lks. dist., marked $\frac{1}{4}$ S 16 P T.
	A Fir, 36 ins. diam., bears N.59'W., 34 lks. dist., marked $\frac{1}{4}$ S 17 P T.
	I again make search for old $\frac{1}{4}$ Sec. cor., but can find no trace of same.
46.45	Creek, 1 lk. wide, course SE. Ascend along East slope.
49.00	Ravine, course SE. Ascend NE. slope.
57.00	Ridge, bears NW. and SE. Descend SW. slope.
78.10	Creek, 2 lks. wide, course SE. Along East slope.
81.44	Intersect the cor. of Secs. 16, 17, 20 and 21, which is a decayed post, marked and witnessed as described by the Surveyor General, except that the NE. bearing tree is dead.
	I destroy this cor. and reestablish it in the same place for the cor. of Secs. 16 and 17 only, as follows:
	Set a Serpentine stone, 15x8x6 ins., 10 ins. in the ground, for cor of Secs. 16 and 17, only, marked with