

Extension Survey of the
Subdivision of T. 32 S., R. 3 W.
Same Deputy and Contract.

CHAINS

NOTE:

Retracements of the exteriors of this township developed the fact that the South and East boundaries were out of limits for alignment and measurement. I resurveyed these two boundaries setting new cor. at legal distances, on which to close the extension survey of the subdivisions.

From the cor. of Secs. 25 and 36, on the East Bdy. of the Tp., I run a Sectional Correction line West, between Secs. 25-36, 26-35, 27-34, 28-33, 29-32 and 30-31, to a closing on the East Bdy. of T. 32 S., R. 4 W.

From the cor. of Secs. 25, 26, 35 and 36, I run a Sectional Guide Meridian, North, between Secs. 25-26, 23 and 24, to an intersection with the South Bdy. of Sec. 13.

South of the Sectional Correction Line, and East of the Guide Meridian, I closed the subdivisions upon the South and East boundaries by random and true lines, throwing the fractional measurements against same; that portion of the Tp. situated to the North and West respectively of said auxiliary lines, I subdivided in the regular manner.

At the corner of Secs. 25 and 36.

Thence I run

West, on a Sectional Correction line, bet. Secs. 25 and 36.

Descend along creek bottom, through dense timber and undergrowth.

12.00 Cow Creek, 15 lks. wide, course N.75*W. Ascend NE slope.

25.70 Spur, slopes North. Descend West slope.

33.30 Creek, 10 lks. wide, course NE. Ascend SE. slope.

38.00 Top of steep ascent. Along South slope.

40.00 Set a Serpentine stone, 18x14x6 ins., 12 ins. in the ground, for $\frac{1}{4}$ Sec. cor. marked $\frac{1}{4}$ on North face, from which

A Fir, 40 ins. diam., bears N.15*W., 30 lks. dist., marked $\frac{1}{4}$ S 25 B T.

A Fir, 40 ins. diam., bears S.27*W., 59 lks. dist., marked $\frac{1}{4}$ S 36 B T.

42.10 Creek, 1 lk. wide, course SE. Ascend East slope.

56.00 Spur, slopes South. Descend SW slope.

61.65 Ravine, course South. Ascend East slope.

72.70 Spur, slopes SE. Descend SW. slope.