

Extension Survey of the Subdivision of T. 32 S., R. 3 W.

CHAINS

77.60

Ravine, course SE. Ascend NE slope.

80.00

Set a Serpentine stone, 18x12x7 ins., 12 ins. in the ground, for cor. of Secs. 25, 26, 35 and 36, marked with 1 notch on East and South edges, from which

A Fir, 40 ins. diam., bears N.55°E., 54 lks.

dist., marked T 32 S R 3 W S 25 B T.

A Fir, 40 ins. diam., bears S.15°E., 10 lks.

dist., marked T 32 S R 3 W S 36 B T.

A Fir, 48 ins. diam., bears S.35°W., 27 lks.

dist., marked T 32 S R 3 W S 35 B T.

A Fir, 54 ins. diam., bears N.44°W., 57 lks.

dist., marked T 32 S R 3 W S 26 B T.

Land, mountainous.

Soil, decomposed granite; 3rd rate.

Timber, Fir and Hemlock.

Undergrowth, Hemlock, Fir, Arrowwood and Rhododendron.

September 24, 1913.

At the corner of Secs. 25, 26, 35 and 36.

Thence I run

West, on a Sectional Correction line, between Secs. 26 and 35.

Ascend SE. slope, through dense timber and undergrowth.

26.50

Summit of Red Mountain ridge, between Cow and Applegate creeks, bears North and South. Descend West slope.

40.00

Set a serpentine stone, 15x10x6 ins., 10 ins. in the ground, for $\frac{1}{4}$ Sec. corner, marked $\frac{1}{4}$ on North face, from which

A Fir, 36 ins. diam., bears N.70°E., 16 lks.

dist., marked $\frac{1}{4}$ S 26 B T.

A Fir, 36 ins. diam., bears S.18°W., 6 lks.

dist., marked $\frac{1}{4}$ S 35 B T.

Descend NE. slope.

52.15

Creek, 1 lk. wide, course NW.