

Extension Survey of the Subdivision of T. 32 S., R 3 W.

CHAINS	
1.15	Creek, 1 lk. wide, course.W.
17.00	Applegate Creek, 20 lks. wide, course NE. Descend along E. slope.
30.50	Wagon road, bears N. 25* E. and S. 25* W.
35.00	Begin ascent of SE. slope.
40.00	Set a granite stone, 15x8x6 ins., 10 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; from which A fir, 36 ins. diam., bears N. 55* E., 61 lks. dist., Marked $\frac{1}{4}$ S 22 B T. A fir, 28 ins.diam., bears N. 14* W., 74 lks dist., marked $\frac{1}{4}$ S 21 B T.
42.40	Spur, slopes E. Along E. slope.
48.25	Ravine, course E.
51.10	Spur, slopes E.
54.35	Creek, 1 lk. wide, course E.
55.10	Spur, slopes S. 60* E.
56.30	Ravine, course SE.
60.10	Spur, slopes SE.
62.00	Ludwig's house, bears E. 20 chs. dist.
74.40	Creek, 2 lks. wide, course SE.
88.75	Spur, slopes SE.
95.60	Spur, slopes E.
99.02	Intersect S. bdy. of sec. 15, N. 89* 48' E., 12.90 chs. from the cor. of secs. 15 and 16, previously described. At the point of intersection, I Set a granite stone, 18x8x6 ins., 12 ins. in the ground, for closing cor. of secs. 21 and 22, marked C C on S. with 3 grooves on E. face; from which A fir, 40 ins.diam., bears S. 43* E., 56 lks. dist., marked T 32 S R 3 W S 22 B T. A fir, 18 ins.diam., bears S. 50* W., 173 lks. dist., marked T 32 S R 3 W S 21 B T.