

Extension Survey of the Subdivision of T. 32 S., R 3 W.

CHAINS

Undergrowth, snow brush, lilac and fir.
Sky was overcast at noon; lat. observation impossible.
October 14, 1913.

October 16: At the cor. of sec. 29, 30, 31 and 32.

Thence I run

N. 0° 3' W., bet secs. 29 and 30.

Ascend SW. slope, through dense timber.

- 1.60 Yellow pine, 40 ins. diam., marked with 2 notches on N. and S. sides.
- 8.00 Ridge, Umpqua divide, bears NW. and SE. Along N. slope.
- 14.00 Begin descent of NE. slope.
- 22.00 Ridge, divide bet. Applegate and Dismal creeks, on NE. slope.
- 40.00 Set a granite stone, 14x10x8 ins., 9 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; from which
 - A fir, 6 ins. diam., bears N. 22° E., 13 lks. dist., marked $\frac{1}{4}$ S. 29 B T.
 - A fir, 24 ins. diam., bears S. 58° W., 19 lks. dist., marked $\frac{1}{4}$ S 30 B T.
- 40.60 Spur, slopes NW.
- 57.90 Creek, 1 lk. wide, course N. 20° E.
- 73.30 Creek, 3 lks. wide, course E.
- 74.70 Spring branch, course E.
- 80.00 Set a serpentine stone, 15x 10x 6 ins., 10 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, marked with 2 notches on S. and 5 notches on E. edge; from which
 - A madrona, 6 ins. diam., bears N. 7° E., 16 lks. dist., marked T 32 S R 3 W S 20 B T.
 - A chinquapin, 12 ins. diam., bears S. 3° E., 56 lks. dist., marked T 32 S R 3 W S 29 B T.