

Extension Survey of the Subdivision of T. 32 S., R. 3 W.

CHAINS

Point of Intersection falls on a granite rock in place, 30
x24x12 ins., above ground, on which I cut a cross
(x) at exact point for closing cor. of secs. 19 and 30.
and mark C C; E, with 4 grooves N., and 2 grooves S. of
cross from which

A Fir, 36 ins. diam., bears N. 89* E., 122 lks. dist.,
marked T 32 S R 3 W S 19 B T.

A Fir, 40 ins. diam., bears S. 82* E., 112 lks. dist.,
marked T 32 S R 3 W S 30 B T.

Land, mountainous.

Soil, stony clay loam; 3rd rate.

Timber, fir, cedar and hemlock.

Undergrowth, rhododendron, fir and hemlock.

October 21, 1913.

October 23: At the cor. of secs. 19, 20, 29 and 30.

Thence I run

N. 0* 3' W., bet secs 19 and 20.

Descend NE. slope, through dense timber and undergrowth.

1.25 Ravine, course SE. Ascend S. slope.

9.75 Ridge, divide bet. Dismal and Snow creeks, bears E. and W.

Gradually descend NE. slope.

12.00 Spur, slopes NE.

18.90 Creek, 2 lks. wide, course NW.

40.00 Set a serpentine stone, 18x10x6 ins., 12 ins. in the
ground, for $\frac{1}{2}$ sec. cor., marked $\frac{1}{2}$ on W. face; from which

A Fir, 12 ins. diam., bears S. 29* E., 37 lks. dist.,
marked $\frac{1}{2}$ S 20 B T.

A Fir, 8 ins. diam., bears S. 85* W., 38 lks. dist.,
marked $\frac{1}{2}$ S 19 B T.

48.60 Ravine, course W.

51.00 Spur, slopes NW.

57.90 Creek, 2 lks. wide, course W.

83.00 Enter old slashing, bears NW. and SE.