

7th Stand. Parallel S., R. 4 W.

CHAINS

- 75.00 Top of ridge, runs N. and S.
- 80.00 Set post corner to secs. 31 and 32, from which,
 A Fir, 30 ins. diam., N.50*W., 29 lks. dist.
 A Fir, 24 ins. diam., N.48*E., 36 lks. dist.
- Country, broken and mountainous. Brushy.
 Timber, principally Fir, some Pine.
 Land, third grade.
-
- West bet. secs. 6 and 31.
- Va. 18*40'E.
- 40.00 Set post for $\frac{1}{4}$ sec. corner, from which,
 A Fir, 18 ins. diam., N.30*E., 19 lks. dist.
 A Fir, 18 ins. diam., S.27*W., 18 lks. dist.
- 57.50 Top of ridge runs NE and SW.
- 80.00 Set post for corner to Tp. 32, S. R. 4 and 5 W.
 A Fir, 12 ins. diam., N.41*E., 18 lks. dist.
 A Fir, 9 ins. diam., N.68*W., 19 lks. dist.
- After diligent search I failed to find the corner and
 establish the one as described above.
 Witness trees evidently destroyed by fire.
 Country, very broken and mountainous.
 Timber, principally Fir.
 Land, third grade.

Thursday, Aug. 28, 1879

Subdivisions, T. 32 S., R. 4 W.
 As surveyed by Carl S. Nicklin, Deputy Surveyor
 Under Contract No. 664, dated May 23, 1896.

The S. bdy. of this Tp.--viz., the 7th Stand. Parallel
 S.--being incorrect in position as is indicated by the
 closing of the E. bdy. I proceed to run a sectional
 correction line, as follows:
 I begin at the corner of secs. 30, 31, 36 and 25, which
 I established Aug. 17, 1897.