

Subdivisions, T. 32 S., R. 4 W.

CHAINS

This corner is on a hillside sloping SE. about 50 ft. above creek.

Land, mountainous.

Soil, third and fourth rate.

Timber, Fir, Cedar, Pine, Chinquapin and Madrona.

Land, mountainous or heavily timbered, 80.00 chs.

West on a true line, bet. secs. 26 and 35.

Asc. spur.

- 4.25 Top of spur, sloping SW. 50 ft. above sec. corner; desc. along NW. side of spur.
- 27.55 To top of ridge, bearing N.80°E., and S.80°W., trail follows top of ridge; this point is about 75 ft. below spur. Thence, along top of ridge.
- 40.00 Set a basalt sone, 12 x 8 x 8 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ N. face; from which,
- A Cedar, 24 ins. diam., bears N.46°W., 75 lks. dist., marked $\frac{1}{4}$ S., B. T.
 - A Cedar, 30 ins. diam., bears S.19°W., 39 lks. dist., marked $\frac{1}{4}$ S., B. T.
- This $\frac{1}{4}$ sec. corner is toward the N. side of ridge.
- Aug. 18: At this $\frac{1}{4}$ sec. corner, I set off 12°51'N. on the decl. arc; and at o h. 4 m., l.m.t., observe the sun on the meridian; the resulting lat. is 42°45'N., which is about 28" less than the proper latitude.
- Thence, gradually desc. along N. side of ridge.
- 55.75 Ravine, sloping N., 50 ft. below $\frac{1}{4}$ sec. corner, asc. spur.
- 58.00 Top of spur, sloping N., 25 ft. above last ravine, desc.
- 65.00 Ravine, sloping N. 50 ft. below last spur; thence along N. side of ridge; gradually asc.
- 80.00 Set a basalt sone, 14 x 8 x 6 ins., 9 ins. in the ground, for corner of secs. 26, 35, 34 and 27, marked with 2