

## Subdivisions, T. 32 S., R. 4 W.

| CHAINS |   |
|--------|---|
|        | From the corner of secs. 27, 28, 33, and 34, run West on a true line bet. secs. 28 and 33.  |
|        | Desc.   |
| 7.00   | Enter green timber, bearing N. and S.   |
| 27.79  | A Fir, 16 ins. diam., on line. I mark with 2 notches on E. and W. sides.  |
| 40.00  | Set a basalt sone, 14 x 10 x 6 ins., 9 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on N. face, from which,<br>A live Oak, 8 ins. diam., bears S.38*E., 14 lks. dist., marked $\frac{1}{4}$ S., B. T.<br>A Fir, 40 ins. diam., bears N.63*W., 15 lks. dist., marked $\frac{1}{4}$ S., B. T.<br>This $\frac{1}{4}$ sec. corner is on a hillside sloping W., about 800 ft. below sec. corner. |
| 42.55  | Trail down Hogum Creek, bears N. and S.<br>From this point, a miner's cabin bears S., 75 lks. dist.   |
| 45.75  | Creek, 1 lk. wide, course, S.80*W., 25 ft. below $\frac{1}{4}$ sec. corner.   |
| 47.50  | Top of spur, sloping S. 80*W.   |
| 51.75  | Creek, 4 lks. wide, C. N., 50 ft. below last creek.<br>Asc.   |
| 53.42  | Trail, bears N. and S., 40 ft. above creek.   |
| 55.25  | Top of spur, sloping N., 25 ft. above trail; desc.  |
| 56.06  | Creek, 1 lk. wide, C. N., 20 ft. below spur; asc. spur.   |
| 65.00  | Top of spur sloping N., 200 ft. above last creek; desc. into canyon.  |
| 74.50  | Bottom of canyon bears NW. and SE, 150 ft. below last spur; asc. spur.  |
| 78.00  | Top of spur, sloping NW., 25 ft. above canyon; desc.  |
| 80.00  | Set a Yew post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for corner of secs. 28, 33, 32 and 29, marked T. 32 S., S. 28 on NE., R. 4 W., S. 33 on SE., S.32 on  |