

## Subdivisions, T. 32 S., R. 4 W.

CHAINS	
	the ground, for a closing corner of secs. 30 and 31, marked
	C. C., T. 32 S., R. 4 W. on E., S. 30 on N., and S. 31 on S. faces, with 1 groove on S. and 5 grooves on N. faces; from which,
	A Madrona, 10 ins. diam., bears S.62*E., 37 lks. dist., marked T. 32 S., R. 4 W., S. 31, B. T.
	A Fir, 12 ins. diam., bears N.48*E., 20 lks. dist., marked T. 32 S., R. 4 W., S. 30, B. T.
	This corner is on top of spur, sloping S; thence, I run East on a true line, bet. secs. 30 and 31; desc.
9.04	Creek, 2 lks. wide, C. SW., 125 ft. below top of spur; asc. spur.
19.75	Top of spur, slopes SW., 100 ft. above creek; desc.
25.00	Ravine, C. SW., 50 ft. below top of last spur; asc. spur.
27.00	Top of spur, slopes SW., 50 ft. above ravine. Desc. into canyon.
29.75	Set a Fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for $\frac{1}{2}$ sec. corner, marked $\frac{1}{2}$ S. on N. face, from which,
	A Fir, 20 ins. diam., bears N.18 $\frac{1}{2}$ *E., 44 lks. dist., marked $\frac{1}{2}$ S., B. T.
	A Fir, 6 ins. diam., bears S.72*W., 62 lks. dist., marked $\frac{1}{2}$ S., B. T.
	This corner is on a hillside, sloping SE., 50 ft. below top of spur.
33.00	Bottom of canyon, 50 ft. below $\frac{1}{2}$ sec. corner, bears N. and S.; asc. spur.
38.00	Top of spur, slopes S., 75 ft. above bottom of canyon; desc.
44.50	Creek, 1 lk. wide, C. S., 75 ft. below top of spur; asc. spur.