

Subdivisions, T. 32 S., R. 4 W.

CHAINS

Set a basalt sone, 12 x 10 x 10 ins., 8 ins. in the ground, for standard corner of secs. 31 and 32, marked S. C. on N., with 1 groove on W., and 5 grooves on E. faces; from which,

A Fir, 18 ins. diam., bears N.48*E., 36 lks. dist., marked T. 32 S., R. 4 W., S. 32, B. T.

A Fir, 24 ins. diam., bears N.50*W., 29 lks. dist., marked T. 32 S., R. 4 W., S. 31, B. T.

East on a blank line, on S. bdy. of sec. 32.

38.55 To a point, 6 lks. S. of the standard $\frac{1}{4}$ sec. corner; post destroyed; bearing trees standing from which I reestablish this $\frac{1}{4}$ sec. corner as follows:

Set a basalt sone, 14 x 10 x 8 ins., 9 ins. in the ground for standard $\frac{1}{4}$ sec. corner, marked S.C., $\frac{1}{4}$ on N. face; from which,

A Cedar, 16 ins. diam., bears S.45*E., 25 lks. dist., marked S. C. $\frac{1}{4}$ S., B. T.

A Fir, 20 ins. diam., bears N.68*W., 10 lks. dist., marked S. C. $\frac{1}{4}$ S., B. T.

78.27 To a point, 10 lks. S. of the standard corner of secs. 32 and 33 which is a post 4 ins. sq., 24 ins. above ground, marked and witnessed as described by the surveyor general.

East on a blank line, on the S. bdy. of sec. 33.

39.86 To a point, 2 lks. S. of the standard $\frac{1}{4}$ sec. corner which is a post, 20 ins. above ground, 3 ins. sq., marked and witnessed as described by the surveyor general.

78.11 To a point, 3 lks. S. of the standard corner of secs. 33 and 34, which is a post 4 ins. sq., 24 ins. above ground, marked and witnessed as described by the surveyor general.

Aug. 20, 1897.
