

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 32 S., R. 4 W.

CHAINS

bearing trees only, are standing, from which reestablish this $\frac{1}{4}$ sec. corner as follows:

Set a basalt stone, 16x14x8 ins., 9 ins. in the ground, for standard $\frac{1}{4}$ sec. corn., marked SC $\frac{1}{4}$ on N. face, from which,

A Madrona, 6 ins. diam., bears N.45*W., 24 lks. dist., marked S C $\frac{1}{4}$ S B T.

A Cedar, 8 ins. diam., bears S.80*E., 29 lks. dist., marked S C $\frac{1}{4}$ S B T.

76.74 To a point, 21 lks. N. of the standard corner of T. 32 S., Rs. 3 and 4 W., which is a cedar post, 4 ins. sq., 24 ins. above ground, marked and witnessed as described by the surveyor general.

Aug. 21, 1897

From the corner of secs. 25, 26, 35 and 36, which I set Aug. 18, 1897, I run

South, 0*1'E., on a true line bet. secs. 35 and 36. Desc.

6.35 Creek, 3 lks. wide, C. SW., 75 ft. below sec. corner. Asc. along hillside sloping westerly.

17.04 Creek, 5 lks. wide, C. W., 20 ft. above last creek.

34.00 Top of spur, sloping S.20*W., 100 ft. above last creek. Descend.

40.00 Set a basalt stone, 12 x 8 x 8 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on W. face; from which,

A Cedar, 20 ins. diam., bears N.75*E., 99 lks. dist., marked $\frac{1}{4}$ S B T.

A Pine, 30 ins. diam., bears S.75*W., 17 lks. dist., marked $\frac{1}{4}$ S B T.

This corner is on a hillside sloping SE., 25 ft. below top of spur.