

Subdivisions, T. 32 S., R. 4 W.

CHAINS

From the corner of secs. 35 and 36, 25 and 26, I run North 0°1'W., on a true line bet. secs. 25 and 26.

Asc.

7.50 Top of ridge bears NE. and SW., 50 ft. above sec. corner. Trail bears NE. and SW. Desc.

21.24 Creek, 2 lks. wide, C. N.70°W., 100 ft. below top of ridge. Asc. spur.

34.50 Top of spur, slopes NW. 50 ft. above creek, desc.

40.00 Set a basalt stone, 20 x 12 x 8 ins., 15 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on W. face, from which,

A Cedar, 16 ins. diam., bears N.54°E., 26 lks. dist., marked $\frac{1}{4}$ S., B. T.

A Cedar, 10 ins. diam., bears S.72°W., 14 lks. dist., marked $\frac{1}{4}$ S., B. T.

This corner is on a hillside sloping N. 75 ft. below top of spur.

47.95 Creek, 2 lks. wide, C. W., 100 ft. below $\frac{1}{4}$ sec. corner.

49.25 Creek, 1 lk. wide, C. W., asc. spur.

50.50 Top of spur, slopes SW. 25 ft. above creeks, desc.

53.54 Creek, 1 lk. wide, C. W., 20 ft. below top of spur, asc.

80.00 Set a basalt stone, 12 x 10 x 8 ins., 8 ins. in the ground, for corner of secs. 23, 24, 25 and 26, marked with 2 notches on S., and 1 notch on E. edges; from which,

A Pine, 30 ins. diam., bears N.43°E., 30 lks. dist., marked T. 32 S., R. 4 W., S. 24, B. T.

A Pine, 30 ins. diam., bears S.58°E., 52 lks. dist., marked T. 32 S., R. 4 W., S. 25, B. T.

A Pine, 18 ins. diam., bears S.56°W., 59 lks. dist., marked T. 32 S., R. 4 W., S. 26, B. T.

A Fir, 6 ins. diam., bears N.58°W., 50 lks. dist.,