

Subdivisions, T. 32 S., R. 4 W.

| CHAINS | |
|--------|--|
| 26.00 | Top of spur, slopes W., 25 ft. above last creek; desc. |
| 27.72 | Creek, 1 lks. wide, C. W., 25 ft. below top of last spur; asc. spur. |
| 40.00 | <p>Set a basalt stone, 14 x 8 x 6 ins., 9 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on W. face; from which,</p> <p>A Fir, 20 ins. diam., bears N.70°E., 12 lks. dist., marked $\frac{1}{4}$ S., B. T.</p> <p>A Cedar, 12 ins. diam., bears S.88°W., 17 lks. dist., marked $\frac{1}{4}$ S., B. T.</p> |
| | This corner is on the S.W. slope of spur, 100 ft. above creek. |
| 41.00 | Top of spur, slopes W., 25 ft. above $\frac{1}{4}$ sec. corner; desc. |
| 50.07 | Creek, 1 lks. wide, C. west, 50 ft. below top of last spur; asc. spur. |
| 65.00 | Top of spur, slopes W., 100 ft. above creek, thence along W. slope of spur. |
| 80.00 | <p>Set a Fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for corner of secs. 11, 12, 13 and 14, marked T. 32 S., S. 12 on NE., R. 4 W., S. 13 on SE., S. 14 on SW., and S. 11 on NW. faces, with 1 notch on the E. and 4 notches on S. edges; from which,</p> <p>A Fir, 20 ins. diam., bears N.7°E., 66 lks. dist., marked T. 32 S., R. 4 W., S. 12, B. T.</p> <p>A Fir, 18 ins. diam., bears S.46°E., 64 lks. dist., marked T. 32 S., R. 4 W., S. 13, B. T.</p> <p>A Fir, 24 ins. diam., bears S.40°W., 144 lks. dist., marked T. 32 S., R. 4 W., S. 14, B. T.</p> <p>A Fir, 20 ins. diam., bears N.70°W., 102 lks. dist., marked T. 32 S., R. 4 W., S. 11, B. T.</p> |
| | Land, mountainous. |
| | Soil, third and fourth rate. |
| | Timber, scattering Fir, Cedar, Hemlock, Madrona, Yew, |