

Subdivisions, T. 32 S., R. 4 W.

CHAINS

- 86.10 Creek, 6 lks. wide, C. S. 80°E., 400 ft. below $\frac{1}{2}$ sec. corner; asc.
- 98.88 Intersect 7th Standard Parallel S., 28.55 chs. W. of the standard corner of secs. 34 and 35 which is a post 4 ins. sq., 15 ins. above ground, marked and witnessed as described by the surveyor general; at point of intersection,
Set a basalt stone, 10 x 8 x 8 ins., 8 ins. in the ground for a closing corner of secs. 34 and 35, marked C. C. on N. face, with 4 grooves on W. and 2 grooves on E. faces; from which,
A Fir, 24 ins. diam., bears N. 45°E., 96 lks. dist., marked T. 32 S., R. 4 W., S. 35 B. T.
A Fir, 30 ins. diam., bears N. 44°W., 50 lks. dist., marked T. 32 S., R. 4 W., S. 34, B. T.
This corner is on top of a spur sloping E., 200 ft. above creek.
Land, mountainous.
Soil, third and fourth rate.
Timber, Fir, Cedar, Pine, Hemlock and Chinquapin.
Dense undergrowth of Rhododendron, Manzanita, Yew and Ocean-spray.
Land, mountainous, heavily timbered or covered with dense undergrowth, 98.88 chs.
-
- North 0°2'W., on a true line, bet. secs. 26 and 27.
Asc. spur.
- 8.50 Top of spur, slopes N. 20°E., 25 ft. above sec. corner; desc.
- 20.75 Same spur, slopes S. 20°W., 175 ft. below sec. corner.
Desc. on NE. slope of spur.
- 40.00 Set a basalt stone, 14 x 10 x 8 ins., 9 ins. in the ground, for $\frac{1}{2}$ sec. corner, marked $\frac{1}{2}$ on N. face; from which,