

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 32 S., R. 4 W.

CHAINS

40.00

Set a Pine post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ S. on W. face, from which,

A Madrona, 6 ins. diam., bears N.73*E., 10 lks. dist., marked $\frac{1}{4}$ S., B. T.

A Fir, 48 ins. diam., bears N.15*W., 23 lks. dist., marked $\frac{1}{4}$ S., B. T.

This $\frac{1}{4}$ sec. corner is on the SW. slope of spur, 125 ft. above creek.

45.75

Top of spur, slopes NW., 75 ft. above $\frac{1}{4}$ sec. corner; desc.

51.10

Creek, 15 lks. wide, C. N.75*W., 150 ft. below top of spur; asc.

53.78

Creek, 1 lk. wide, C. S.60*W., 25 ft. above last creek.

80.00

Set a Fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for corner of secs. 14, 15, 22, and 23, marked T. 32 S., S. 14 on NE., R. 4 W., S. 23, on SE., S. 22 on SW., and S. 15 on NW. faces; with 2 notches on E. and 3 notches on S. edges; from which,

A Fir, 20 ins. diam., bears N.32*E., 27 lks. dist., marked T. 32 S., R. 4 W., S. 14, B. T.

A Fir, 24 ins. diam., bears S.30*E., 57 lks. dist., marked T. 32 S., R. 4 W., S. 23, B. T.

A Fir, 24 ins. diam., bears S.52 $\frac{1}{2}$ *W., 17 lks. dist., marked T. 32 S., R. 4 W., S. 22, B. T.

A Fir, 24 ins. diam., bears N.45*W., 69 lks. dist., marked T. 32 S., R. 4 W., S. 15, B. T.

This corner is on the S. slope of spur, 300 ft. above last creek.

Land, mountainous.

Soil, third rate.

Timber, Fir, Pine, Cedar, Yew, and Maple.

Dense undergrowth of Rhododendron, Madrona and Chinquapin.

Land, mountainous, or heavily timbered, 80.00 chs.