

## County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 32 S., R. 4 W.

## CHAINS

A Fir, 30 ins. diam., bears N.22\*E., 20 lks. dist., marked T. 32 S., R. 3 W., S. 6, B. T.

A Fir, 24 ins. diam., bears S.8\*E., 214 lks. dist., marked T. 32 S., R. 3 W., S. 7, B. T.

A Fir, 36 ins. diam., bears S8 $\frac{1}{2}$ \*W., 166 lks. dist., marked T. 32 S., R. 4 W., S. 12, B. T.

A Fir, 20 ins. diam., bears N.18\*W., 108 lks. dist., marked T. 32 S., R. 4 W., S. 1, B. T.

Therefore, this line bears N.89\*52\*W.

Since the S. bdy. of sec. 1 was found to be short in measurement, I proceed as follows:

From the corner of secs. 10, 11, 14 and 15, I run North 0\*2\*W., on a true line, bet. secs. 10 and 11. Along W. slope of spur.

- 6.00 Top of spur, slopes N.60\*W.  
Enter green timber, bears N.60\*W., and S.60\*E; desc.
- 15.05 A Fir, 60 ins. diam., on line, I mark with 2 notches on N and S. sides.
- 20.50 Ravine, C. N.20\*W., 300 ft. below sec. corner.
- 32.48 Creek, 2 lks. wide, C. N.80\*W., 500 ft. below sec. corner.  
Asc.
- 33.75 Creek, 1 lk. wide, C. S.20\*W., 20 ft. above last creek.
- 40.00 Set a Fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for  $\frac{1}{4}$  sec. corner, marked  $\frac{1}{4}$  S. on W. face; from which,
- A Madrona, 6 ins. diam., bears N.36\*E., 6 lks. dist., marked  $\frac{1}{4}$  S., B. T.
- A Madrona, 8 ins. diam., bears S.32\*W., 18 lks. dist., marked  $\frac{1}{4}$  S., B. T.
- This corner is on the S. slope of mountain, 100 ft. above creek.