

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 32 S., R. 4 W.

CHAINS

This corner is on a steep S. slope, 50 ft. above bottom of ravine.

44.75 Top of ridge, bears E. and W., 75 ft. above $\frac{1}{4}$ sec. corner; desc.

58.96 Creek, 1 lk. wide, C. NW., 400 ft. below top of ridge; asc. spur.

60.25 Top of spur, slopes NW. 25 ft. above last creek; desc.

62.50 Creek, 2 lks. wide, C. N.60*W., 25 ft. below last spur; asc. spur.

66.25 Top of spur, slopes W., 100 ft. above creek; desc.

79.73 Intersect E. and W. line, 452 lks. N.89*50'W. of the corner of secs. 1, 2, 11 and 12, which I find in a delapidated condition; and which I reestablish from the bearing tree in sec. 11, the only one standing, as follows:

Set a Fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for a corner of secs. 1 and 2, marked T. 32 S., S. 1 on NE., and R. 4 W., S. 2 on NW. faces; with 1 notch on E. edge; from which

A Fir, 6 ins. diam., bears N.27*E., 23 lks. dist., marked T. 32 S., R. 4 W., S. 1, B. T.

A Fir, 14 ins. diam., bears N.63*W., 70 lks. dist., marked T. 32 S., R. 4 W., S. 2, B. T.

At point of intersection, 452 lks. N.89*50'W., of this corner,

Set a Fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for a closing corner of secs. 11 and 12, marked C. C. T. 32 S., R. 4 W., on S., S. 12 on E., and S. 11 on W., with 1 groove on E., and 5 grooves on S. faces; from which,

A Fir, 6 ins. diam., bears S.9*E., 12 lks. dist., marked T. 32 S., R. 4 W., S. 12, B. T.

A Fir, 24 ins. diam., bears S.55*W., 75 lks. dist., marked T. 32 S., R. 4 W., S. 11, B. T.