

Subdivisions, T. 32 S., R. 4 W.

CHAINS	
	marked $\frac{1}{4}$ S., B. T. A Fir, 20 ins. diam., bears South, 45 lks. dist., marked $\frac{1}{4}$ S., B. T.
77.18	To a point 91 lks. S. of the corner of secs. 2, 3, 34 and 35, which is a post 24 ins. above ground, marked and witnessed as described by the surveyor general. Therefore, this line bears N.89°21'E.
	<hr/> At corner of secs. 27, 28, 33 and 34, thence, I run South, 0°2'E., on a true line, bet. secs. 33 and 34. Asc. spur.
27.75	Top of spur, slopes W., 175 ft. above sec. corner; desc.
40.00	Set a basalt stone, 14 x 8 x 8 ins., 9 ins., in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on W. face; from which A Fir, 8 ins. diam., bears S.29°E., 57 lks. dist., marked $\frac{1}{4}$ S., B. T. A Live Oak, 6 ins. diam., bears S.7 $\frac{1}{2}$ °W., 70 lks. dist., marked $\frac{1}{4}$ S., B. T. This corner is on the S. slope of spur, 250 ft. below top.
42.50	Enter green timber, bears NE. and SW.
51.50	Ravine, C. W., 100 ft. below $\frac{1}{4}$ sec. corner; asc.
58.00	Top of ridge, bears NE. and SW. This is the divide bet. Starvout and Grave Creeks, 75 ft. above ravine; desc.
77.20	Water ditch, which conducts water from Grave Creek to Starvout Creek for mining purposes bears NE. and SW. 50 ft. below top of ridge.
77.55	Creek, 3 lks. wide, C. SW., 25 ft. below ditch; asc. spur.
82.30	Top of spur, slopes W., 50 ft. above creek; desc.
86.50	Trail, bears E. and W., 75 ft. below top of spur.