

Subdivisions, T. 32 S., R. 4 W.

CHAINS	
99.05	<p>Intersect 7th Standard Parallel S., 29.60 chs. W. of the standard corner of secs. 33 and 34, which is a post 4 ins. sq., 24 ins. above ground, marked and witnessed as described by the surveyor general.</p> <p>Set a basalt stone, 12 x 10 x 8 ins., 8 ins. in the ground for a closing corner of secs. 33 and 34, marked C. C., T. 32 S., R. 4 W., on N., S. 33 on W., and S. 34 on E. faces; with 3 grooves on E. and W. faces, from which</p> <p style="padding-left: 40px;">A Fir, 10 ins. diam., bears N.8°E., 32 lks. dist., marked T. 32 S., R. 4 W., S. 34, B. T.</p> <p style="padding-left: 40px;">A Fir, 30 ins. diam., bears N.37½°W., 30 lks. dist., marked T. 32 S., R. 4 W., S. 33, B. T.</p> <p>This closing corner is on top of spur sloping S., 100 ft. below trail.</p> <p>Land, mountainous.</p> <p>Soil, third and fourth rate.</p> <p>Timber, Fir, Cedar, Pine, Chinquapin, Yew and Live Oak.</p> <p>Dense undergrowth of Manzanita, Ocean-spray and Yew.</p> <p>Land, mountainous, heavily timbered or covered with dense undergrowth, 99.05 chs.</p>
	<hr/> <p>North, 0°2'W., on a true line, bet. secs. 27 and 28.</p> <p>Desc.</p>
10.00	<p>Enter green timber, bears E. and W.</p>
35.75	<p>Ravine, C. N.20°W., 800 ft. below sec. corner.</p>
37.40	<p>Boulder Creek, 6 lks. wide, C. N.30°W., 25 ft. below ravine; asc. spur.</p>
40.00	<p>Set a basalt stone, 14 x 10 x 8 ins., 9 ins. in the ground for ¼ sec. corner, marked ¼ S. on W. face; from which,</p> <p style="padding-left: 40px;">A Fir, 20 ins. diam., bears N.50°E., 6 lks. dist., marked ¼ S., B. T.</p>