

## Subdivisions, T. 32 S., R. 4 W.

CHAINS	
35.94	Creek, 3 lks. wide, C. E., 400 ft. below top of ridge; asc. spur.
36.75	Top of spur, slopes NE., 25 ft. above last creek; desc.
37.25	Creek, 1 lk. wide, C. SE., 20 ft. below top of last spur; asc.
40.00	<p>Set a Fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for <math>\frac{1}{4}</math> sec. corner, marked <math>\frac{1}{4}</math> S. on W. face, from which</p> <p style="padding-left: 40px;">A Fir, 10 ins. diam., bears S.75*E., 23 lks. dist., marked <math>\frac{1}{4}</math> S., B. T.</p> <p style="padding-left: 40px;">A Fir, 12 ins. diam., bears S.27*W., 69 lks. dist., marked <math>\frac{1}{4}</math> S., B. T.</p> <p>This <math>\frac{1}{4}</math> sec. corner is on the SE. slope of spur, 50 ft. above creek.</p>
47.00	Top of spur, slopes E., 100 ft. above $\frac{1}{4}$ sec. corner; desc.
56.38	Creek, 6 lks. wide, C. E., 200 ft. below top of last spur; asc. spur.
69.50	Top of spur, slopes SE., 125 ft. above creek; desc.
75.75	Ravine, C. S.30*E., 50 ft. below top of last spur; asc. spur.
77.50	Top of spur, slopes S.30*E., 50 ft. above ravine; desc.
80.00	<p>Set a Madrona post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for a corner of secs. 9, 10, 15 and 16, marked</p> <p>T. 32 S., S. 10 on NE., R. 4 W., S. 15 on SE., S. 16 on SW., and S. 9 on NW. faces, with 3 notches on the E. and 4 notches on S. edges; from which</p> <p style="padding-left: 40px;">A Fir, 30 ins. diam., bears N.33<math>\frac{1}{2}</math>*E., 100 lks. dist., marked T. 32 S., R. 4 W., S. 10, B. T.</p> <p style="padding-left: 40px;">A Fir, 24 ins. diam., bears S.43*E., 83 lks. dist., marked T. 32 S., R. 4 W., S. 15, B. T.</p> <p style="padding-left: 40px;">A Fir, 36 ins. diam., bears S.42*W., 240 lks. dist., marked T. 32 S., R. 4 W., S. 16, B. T.</p>