

Subdivisions, T. 32 S. R. 4 W.

CHAINS	
40.00	<p>Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ S on W. face; from which</p> <p style="padding-left: 40px;">A Fir, 16 ins. diam., bears N.63*E., 67 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p style="padding-left: 40px;">A Fir, 36 ins. diam., bears N.18*W., 102 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p>This corner is on the N. slope of spur, 350 ft. below top.</p>
52.20	<p>White Horse Creek, 20 lks. wide, C. NW., 200 ft. below $\frac{1}{4}$ sec. corner.</p> <p>Asc. spur, gradually.</p>
53.50	<p>Wagon road, bears NW. and SE.</p>
55.50	<p>Water ditch, to abandoned mine, bears NW. and SE.</p>
55.96	<p>Trail bears E. and W.</p>
57.00	<p>Top of spur, slopes NW., 50 ft. above White Horse Creek; desc.</p>
58.95	<p>Creek, 2 lks. wide, C. W., 20 ft. below top of last spur; asc. spur.</p>
65.00	<p>Top of spur, slopes W., 75 ft. above last creek; desc.</p>
67.75	<p>Creek, 1 lk. wide, C. SW., 25 ft. below top of spur; asc.</p>
71.25	<p>Intersect E. and W. line, 8.15 chs. S.89*39*W. of the corner of secs. 3, 4, 9 and 10, which is a post 24 ins. above ground, marked and witnessed as described by the surveyor general; and which I reestablish as follows:</p> <p>Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for corner of secs. 3 and 4, marked</p> <p>T 32 S S 3 on NE. and R 4 W S 4 on NW. faces, with 3 notches on E. edge, from which</p> <p style="padding-left: 40px;">A Fir, 30 ins. diam., bears N.75*E., 45 lks. dist., marked T 32 S R 4 W S 3 B T.</p> <p style="padding-left: 40px;">A Madrona, 5 ins. diam., bears N.25*W., 112 lks. dist., marked T 32 S R 4 W S 4 B T.</p>