

Subdivisions, T. 32 S., R. 4 W.

CHAINS

At point of intersection, 8.15 chs. S.89°30'W. of this corner, I

Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for a closing corner of secs. 9 and 10, marked C C T 32 S R 4 W on S., S 9 on W., and S 10 on E. faces, with 5 grooves on S. and 3 grooves on E. faces; from which

A Cedar, 10 ins. diam., bears S.40°E., 34 lks. dist., marked T 32 S R 4 W S 10 B T.

A Madrona, 10 ins. diam., bears S.33°W., 31 lks. dist., marked T 32 S R 4 W S 9 B T.

This corner is on a S. slope, 50 ft. above creek.

Land, mountainous.

Soil, third and fourth rate.

Timber, scattering fir, cedar, madrona, alder and maple.

Dense undergrowth of mountain-balm, rhododendron, vine-maple, huckle-berry, salal-berry and thimble-berry.

Land, mountainous, or covered with dense undergrowth,

71.25 chs.

September 2, 1897.

---

At the corner of secs. 28, 29, 32 and 33

I run

South, 0°3'E., on a true line, bet. secs. 32 and 33.

Asc.

- 1.35 Creek, 1 lks. wide, C. NW., 20 ft. above corner.
- 7.00 Top of spur, slopes W. 125 ft. above sec. corner; desc.
- 21.50 Creek, 1 lks. wide, C. W., 75 ft. below top of last spur; asc. spur.
- 25.00 Top of spur, slopes W., 75 ft. above last creek; desc.
- 34.75 Wagon road, bears NW. and SE.
- 35.85 Water ditch of miners' construction, Bears NW. and SE.
- 36.75 Creek, 6 lks. wide, C. NW., 100 ft. below top of last spur; asc. spur.