

Subdivisions, T. 32 S. R. 4 W.

CHAINS

- 40.00 Set a basalt stone, 14 x 10 x 8 ins., 9 ins. in the ground, for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on W. face; from which
- A Fir, 24 ins. diam., bears N.48*E., 25 lks. dist., marked $\frac{1}{4}$ S BT.
- A Fir, 20 ins. diam., bears S.82*W., 48 lks. dist., marked $\frac{1}{4}$ S B T.
- This corner in on the N. slope of spur, 50 ft. above creek.
- 58.00 Top of spur, slopes NW., 200 ft. above $\frac{1}{4}$ sec. corner; desc.
- 72.50 Ravine, C. W., 75 ft. below last spur; asc. spur.
- 75.00 Top of spur slopes W., 50 ft. above ravine; desc.
- 91.32 Creek, 8 lks. wide, C. N.30*W., 100 ft. below top of spur; asc.
- 99.43 Intersect E. and W. line,--the 7th Standard Parallel South,--31.02 chs. W. of the standard corner of secs. 32 and 33, which is a post, 4 ins. sq., 24 ins. above ground, marked and witnessed as described by the surveyor general.
- Set a basalt stone, 14 x 10 x 8 ins., 9 ins. in the ground for a closing corner of secs. 32 and 33, marked C C on N., with 2 grooves on W. and 4 grooves on E. faces; from which
- A Fir, 14 ins. diam., bears N.18*E., 31 lks. dist., marked T 32 S R 4 W S 33 B T.
- A Fir, 24 ins. diam., bears N.17*W., 25 lks. dist., marked T 32 S R 4 W S 32 B T.
- This corner is on a NE. slope, 100 ft. above creek.
- Land, mountainous.
- Soil, third and fourth rate.
- Timber, fir, cedar, hemlock, pine, madrona, yew and chinquapin.